

ANGLE CONTROL VALVE

TECHNICAL SPECIFICATIONS

SIZE: 15mm to 80mm

BODY MATERIAL: 1CF8, CF8M, CF3M (Others are available on request)

TRIM / SPINDLE: Stainless Steel SS304, SS316, SS316L

END CONNECTION: Female Screwed to BSP or NPT Ends, Flanged ends, Triclover

MATERIAL: Carbon steel, Stainless steel, Monel, Duplex, Alloy 20, Hastelloy B/C, Aluminum Bronze, PFA Lined etc.

LEAKAGE: Drop Tight/Bubble Tight, Class IV ANSI B16, 104, 1976

ACTUATOR BODY: SS 304 Pressed

COVER FLANGE: ASTM A351 Gr. CF8 (SS304) Investment Die-Cast

ACTUATOR SPRING: Spring Steel (IS 4454 Gr. III)

ACTUATOR PORT CONNECTION: 1/4" BSP (NPT on request)

ACTUATOR OPERATING PRESSURE: 3.5 to 7 Bar(g)

ACTUATOR POSITION INDICATOR: NYLON

ACTUATOR OPERATING CYCLES: 350 to 650 Cycles / Hr.



HybridOX
Automation LLP
Inspired By Innovation

MANUFACTURER, SUPPLIER & EXPORTER OF PREMIUM QUALITY INDUSTRIAL CONTROL VALVES



+91 70215 57109
(Call, WhatsApp, SMS)



+91 88500 39676
(Call, WhatsApp, SMS)



sales@hybridox.in
hybridoxautomation@gmail.com



www.hybridox.in



OFFICE: 53, Shree Manoshi Complex, Plot No. 5 & 6, Sector 3,
Opp. Ghansoli Railway Station, Ghansoli (E), Navi Mumbai, (MH) 400701.

