

PNEUMATIC BUTTERFLY VALVE

TECHNICAL SPECIFICATIONS

DESIGN: Wafer type

VALVE SIZE: 50 to 600 mm (2" to 24")

BODY TYPE: Metal to Metal /Double Offset/Triple Offset/Sleeve Design

SEAT LEAKAGE: II to VI (FCI-70.2)

BODY: Cast Iron, Carbon Steel, Stainless Steel, etc.

VANE / DISC: Stainless Steel, (Other on Request)

BODY SLEEVE: Nitrile, EPDM, (Other on Request)

ACTUATOR: Diaphragm, Rotary or Electrical

GLAND PACKING: PTFE V Ring upto 180°C, Grafoil upto 400°C.

KEY FEATURES AND BENEFITS

Heavy Duty Top Guided, Large Variety of Trim Design, Tight Shut-off & Soft Seated Option, Easy Maintenance.

AREAS OF APPLICATIONS

All Industry Segments, Power, Nuclear, Oil & Gas, Refining, Fertilizer, Chemical, Pharmaceuticals, Aerospace, etc.



HybridOX
Automation LLP
Inspired By Innovation

MANUFACTURER, SUPPLIER & EXPORTER OF PREMIUM QUALITY INDUSTRIAL CONTROL VALVES



+91 70215 57109
(Call, WhatsApp, SMS)



+91 88500 39676
(Call, WhatsApp, SMS)



sales@hybridox.in
hybridoxautomation@gmail.com



www.hybridox.in



OFFICE: 53, Shree Manoshi Complex, Plot No. 5 & 6, Sector 3,
Opp. Ghansoli Railway Station, Ghansoli (E), Navi Mumbai, (MH) 400701.

