

# PNEUMATIC FLUSH BOTTOM VALVE

## TECHNICAL SPECIFICATIONS

**DESIGN:** Plug Type

**VALVE SIZE:** 1/2" to 14" (15MM - 350MM)

**PRESSURE RATING:** 150# to 300# other standards are available on request.

**MATERIAL:** Fabricated in Carbon Steel, SS 304, SS 316, SS 304L, SS 316L.

**DESIGN TEMPERATURE:** -20°C to 280°C.

## KEY FEATURES AND BENEFITS

Customized designs as per customer requirement  
High flow capacity and Zero material clogging  
Heavy Duty Construction for longer life  
Temperature sensor attachment in plug

## AREAS OF APPLICATIONS

Petrochemical industry  
Pharmaceutical  
Chemicals  
Process Industry



**HybridOX**  
**Automation LLP**  
*Inspired By Innovation*

**MANUFACTURER, SUPPLIER & EXPORTER OF PREMIUM QUALITY INDUSTRIAL CONTROL VALVES**



+91 70215 57109  
(Call, WhatsApp, SMS)



+91 88500 39676  
(Call, WhatsApp, SMS)



[sales@hybridox.in](mailto:sales@hybridox.in)  
[hybridoxautomation@gmail.com](mailto:hybridoxautomation@gmail.com)



[www.hybridox.in](http://www.hybridox.in)



OFFICE: 53, Shree Manoshi Complex, Plot No. 5 & 6, Sector 3,  
Opp. Ghansoli Railway Station, Ghansoli (E), Navi Mumbai, (MH) 400701.

