

# THREE-WAY CONTROL GLOBE VALVE

## TECHNICAL SPECIFICATIONS

**DESIGN:** ASME B16.34

**BODY FORM:** Globe Type with Tail piece to provide third port

**VALVE SIZE:** 15 to 300 mm (1/2" to 12")

**RATING:** 150 to 1500 ANSI

**TRIM FORM:** Linear, V-Port Skirt Guided

**FLOW CHART:** Linear, On/Off

**SEAT LEAKAGE:** V, V & VI (FCI-70.2 )

**ACTUATOR:** Diaphragm, Piston or Electrical

**ACTUATOR ACTION:** Direct / Reverse Acting

## KEY FEATURES AND BENEFITS

Heavy Duty Top Guided / High Flow Capacity / Easy Maintenance

Large Variety of Trim Design / Tight Shut-off & Soft Seated Option

## AREAS OF APPLICATIONS

All Industry Segments, Power, Nuclear, Oil & Gas,  
Refining, Fertilizer, Chemical, Pharmaceuticals, Aerospace etc.



**HybridOX**  
**Automation LLP**  
*Inspired By Innovation*

**MANUFACTURER, SUPPLIER & EXPORTER OF PREMIUM QUALITY INDUSTRIAL CONTROL VALVES**



+91 70215 57109  
(Call, WhatsApp, SMS)



+91 88500 39676  
(Call, WhatsApp, SMS)



[sales@hybridox.in](mailto:sales@hybridox.in)  
[hybridoxautomation@gmail.com](mailto:hybridoxautomation@gmail.com)



[www.hybridox.in](http://www.hybridox.in)



OFFICE: 53, Shree Manoshi Complex, Plot No. 5 & 6, Sector 3,  
Opp. Ghansoli Railway Station, Ghansoli (E), Navi Mumbai, (MH) 400701.

